

ASHCOR STANDARD ENCLOSED COMBUSTORS

ASHCOR's standard enclosed combustors are made of a stainless steel body and designed to withstand heavy wind, harsh oil and gas environments and other stringent conditions.

Built to promote environmental and site safety, the standard enclosed combustors burn at a maximum rate of 200 MSCFD (140 SCFM instantaneous flow rate) and have distinct features such as minimal noise pollution and reduced radiant heat.



Contact our sales team to purchase an enclosed combustor that best fits your site. [423-498-1988](tel:423-498-1988)

ASHCOR

ASHCOR
FLARES USE FLAME SMART
OR
PROFIRE CONTROLS
& **ASHCOR FLAME ARRESTERS**

STANDARD FEATURES

Gas train controls and monitors gas flow to the burners

Continuous pilot and flame presence monitoring

Pressure based system operation

Combustion Temperature Air Control

Integrated Flame Smart or Profire burner management system

ASHCOR flame arresters

UPGRADE FEATURES

Solar panel functionality for sites without power



ASHCOR 20
2.4 MMBTU/hr

ASHCOR 100
9.2 MMBTU/hr



ASHCOR 200
18.4 MMBTU/hr



View more products online
ashcor.com

Custom fabrication is available based on site and application needs.

PHONE: 423-498-1988

ADDRESS: 4334 North Creek Road
Chattanooga, TN 37406

ASHCOR

ashcor.com

